



**NexaParts B.V.**  
Duurzaamheidstraat 33  
8094SC, Hattemerbroek

**E-MAIL** [info@nexaparts.nl](mailto:info@nexaparts.nl)  
**TEL** +31 38 2024038  
**KVK** 87151227

## Flat waterhose - 32mm - 1-1/4" (roll 50m)

<https://www.nexaparts.com/flat-waterhose-32mm-1-14-roll-50m>

### Specificaties

|                  |                                             |
|------------------|---------------------------------------------|
| Productnummer    | 20400032                                    |
| EAN              | 9503324134433                               |
| Merk             | NexaParts                                   |
| Categorie        | Rubber Hoses                                |
| Style            | Platte waterslang - 32mm - 1-1/4" (Rol 50m) |
| Diepte/lengte    | 5000.00                                     |
| Breedte          | 3.20                                        |
| Hoogte           | 3.20                                        |
| Gewicht          | 11.00 Kg                                    |
| Inner diameter   | 32 mm                                       |
| Length           | Rol (50m)                                   |
| Color            | Blauw                                       |
| Inner diameter   | 32                                          |
| Max length       | 50m                                         |
| Outer Diameter   | 34mm                                        |
| applicable for   | Water en lichte chemicalien                 |
| Barst pressure   | 24 bar                                      |
| Color 2          | Blauw                                       |
| Dimensions       | Volle rol 50m                               |
| Inner surface    | Glad, PVC                                   |
| Insert           | Sterke synthetische textiel inlagen         |
| Material         | PVC                                         |
| Model            | Waterslang Plat oprolbaar                   |
| Outer diameter   | 34 mm                                       |
| Outer surface    | Weer- en verouderingsbestendig blauw PVC    |
| Temperatur range | -10°C / +60°C                               |
| Work pressure    | 8 bar                                       |

### Pluspunten

- + Flat rollable
- + Good wear resistance
- + Lightweight

**Pluspunten**

- + Very small bending radius

**Minpunten**

- Relative low working pressure