



**NexaParts B.V.**  
Duurzaamheidstraat 33  
8094SC, Hattemerbroek

E-MAIL [info@nexaparts.nl](mailto:info@nexaparts.nl)  
TEL +31 38 2024038  
KVK 87151227

## Ventilation-suction hose - Pond hose - PVC - 31,8 x 37,4mm (Per meter)

<https://www.nexaparts.com/ventilation-suction-hose-pond-hose-pvc-31.8-x-37.4mm-per-meter>

### Specificaties

|                  |                                           |
|------------------|-------------------------------------------|
| Productnummer    | 33476                                     |
| EAN              | 9509676761457                             |
| Merk             | NexaParts                                 |
| Categorie        | Rubber Hoses                              |
| Materiaal        | PVC                                       |
| Kleur            | Zwart                                     |
| Style            | Binnendiameter ø31,8 x 37,4mm (Per meter) |
| model            | Luchtslang                                |
| Diepte/lengte    | 100.00                                    |
| Breedte          | 100.00                                    |
| Hoogte           | 100.00                                    |
| Inner diameter   | 31,8 mm                                   |
| Length           | 1m                                        |
| Inner diameter   | 31,8                                      |
| Outer Diameter   | 37,4mm                                    |
| applicable for   | Lucht, Gas, Chemische dampen              |
| Color            | Zwart                                     |
| Color 2          | Zwart                                     |
| Dimensions       | Per Meter                                 |
| Inner surface    | PVC                                       |
| Insert           | Witte harde PVC spiraal                   |
| Material         | PVC                                       |
| Model            | Luchtslang                                |
| Outer diameter   | 37,4 mm                                   |
| Outer surface    | PVC                                       |
| Temperatur range | -10°C / +50°C                             |
| Wall Thickness   | 2,8 mm                                    |

### Pluspunten

- + UL 94 Class V2
- + Weather and aging resistant