



**NexaParts B.V.**  
Duurzaamheidstraat 33  
8094SC, Hattemerbroek

E-MAIL [info@nexaparts.nl](mailto:info@nexaparts.nl)  
TEL +31 38 2024038  
KVK 87151227

## Ventilation-suction hose - Pond hose - PVC - 300 x 314mm (Per meter)

<https://www.nexaparts.com/ventilation-suction-hose-pond-hose-pvc-300-x-314mm-per-meter>

### Specificaties

|                  |                                         |
|------------------|-----------------------------------------|
| Productnummer    | 33497                                   |
| EAN              | 9509177455862                           |
| Merk             | NexaParts                               |
| Categorie        | Rubber Hoses                            |
| Materiaal        | PVC                                     |
| Kleur            | Zwart                                   |
| Style            | Binnendiameter ø300 x 314mm (Per meter) |
| model            | Luchtslang                              |
| Diepte/lengte    | 100.00                                  |
| Breedte          | 100.00                                  |
| Hoogte           | 100.00                                  |
| Inner diameter   | 300 mm                                  |
| Length           | 1m                                      |
| Inner diameter   | 300                                     |
| Outer Diameter   | 314mm                                   |
| applicable for   | Lucht, Gas, Chemische dampen            |
| Color            | Zwart                                   |
| Color 2          | Zwart                                   |
| Dimensions       | Per Meter                               |
| Inner surface    | PVC                                     |
| Insert           | Witte harde PVC spiraal                 |
| Material         | PVC                                     |
| Model            | Luchtslang                              |
| Outer diameter   | 314 mm                                  |
| Outer surface    | PVC                                     |
| Temperatur range | -10°C / +50°C                           |
| Wall Thickness   | 7 mm                                    |

### Pluspunten

- + UL 94 Class V2
- + Weather and aging resistant