



**NexaParts B.V.**  
Duurzaamheidstraat 33  
8094SC, Hattemerbroek

E-MAIL [info@nexaparts.nl](mailto:info@nexaparts.nl)  
TEL +31 38 2024038  
KVK 87151227

## Hydraulic hose - very high pressure - NBR-CM - 9,5 x 19mm (Per meter)

<https://www.nexaparts.com/hydraulic-hose-very-high-pressure-nbr-cm-9.5-x-19mm-per-meter>

### Specificaties

|                  |                                        |
|------------------|----------------------------------------|
| Productnummer    | 33609                                  |
| EAN              | 9507514631450                          |
| Merk             | NexaParts                              |
| Categorie        | Rubber Hoses                           |
| Materiaal        | NBR / CM                               |
| Style            | Binnendiameter ø9,5 x 19mm (Per meter) |
| model            | Hydrauliek slang                       |
| Diepte/lengte    | 100.00                                 |
| Breedte          | 100.00                                 |
| Hoogte           | 100.00                                 |
| Inner diameter   | 9,5                                    |
| Outer Diameter   | 19mm                                   |
| applicable for   | Smeermiddelen, Hydraulische oliën      |
| Barst pressure   | 1320 bar                               |
| Inner diameter   | 9,5 mm                                 |
| Inner surface    | NBR                                    |
| Insert           | Staalinlagen                           |
| Length           | 1m                                     |
| Material         | NBR / CM                               |
| Model            | Hydrauliek slang                       |
| Outer diameter   | 19 mm                                  |
| Outer surface    | CM                                     |
| Temperatur range | -40°C / +100°C                         |
| Wall Thickness   | 4,75 mm                                |
| Dimensions       | Per Meter                              |

### Pluspunten

- + Available in any desired length (with maximum of roll length)
- + ISO 1307, DIN EN 853 1SN, SAE 100 R1 AT