



**NexaParts B.V.**  
Duurzaamheidstraat 33  
8094SC, Hattemerbroek

**E-MAIL** info@nexaparts.nl  
**TEL** +31 38 2024038  
**KVK** 87151227

## Straight Bushing FER - MET FMZ - FMZ209 253060FG

<https://www.nexaparts.com/straight-bushing-fer-met-fmz-fmz209-253060fg>

### Specificaties

|                   |                                                                      |
|-------------------|----------------------------------------------------------------------|
| Productnummer     | FMZ209.253060FG                                                      |
| Merk              | GLT                                                                  |
| Categorie         | Sliding Bearings                                                     |
| afmeting          | 1. Inner diameter:25 2. Outer diameter:30 3. Length:60 4. Bauform:FG |
| Materiaal         | C67, Verenstaal 55Si7                                                |
| Kleur             | Zwart                                                                |
| Style             | 253060FG                                                             |
| model             | Cilinderbus                                                          |
| Model Description | Glijlager (ingespannen)                                              |
| Color             | Zwart                                                                |
| Dimensions        | 1. Inner diameter:25 2. Outer diameter:30 3. Length:60 4. Bauform:FG |
| Dynamic load      | 200 N/mm1116 N/mm2                                                   |
| Friction value    | > 0,5 $\mu$                                                          |
| Material          | C67, Verenstaal 55Si7                                                |
| Model             | Cilinderbus                                                          |
| Rotation speed    | 1 m/s                                                                |
| Static Load       | 350 N/mm1116 N/mm2                                                   |
| Temperatur range  | -200 bis +350 °C'                                                    |

### Pluspunten

+ Tolerance after mounting according to DIN 1498/2485