



NexaParts B.V.
Duurzaamheidstraat 33
8094SC, Hattemerbroek

E-MAIL info@nexaparts.nl
TEL +31 38 2024038
KVK 87151227

Rod End SIBP12S - GIKR12PB - SIKAC12M - Bore 12MM x M12 - BSP/F

<https://www.nexaparts.com/rod-end-sibp12s-gikr12pb-sikac12m-bore-12mm-x-m12-bspf>

Specificaties

Productnummer SIBP12S - GIKR12PB - SIKAC12M

EAN 7440846262287

Merk NexaParts

Categorie Rod Ends

Materiaal ST 52-3 Verzinkt

Kleur Metaal

Style SIBP12S - GIKR12PB - SIKAC12M

model Stangkop onderhoudsplichtig

Gewicht 0.11 Kg

Color Metaal

Material ST 52-3 Verzinkt

Model Stangkop onderhoudsplichtig

B (Inner ring width) 10 mm

Basic load ratings dynamic 10 kN

Basic load ratings statisch 23 kN

C1 max (Rod end width) 8,5 mm

CN Radial internal clearance 0,023 - 0,068 mm

d (Bearing bore) 12 mm

d2 max (Rod end diameter) 34 mm

L3 min (Thread length) 24 mm

Maintenance Nippel No

Maintenance required Yes

Norm DIN ISO 12 240-4-series K, Form F

Thread size M12

Tilting angle 10 ° ?

Total height Rod end (L, L2, L4) 65

Pluspunten

- + DIN ISO 12 240-4-Series K, Form F
- + Easy Essembling
- + Sliding Surface: Steel/bronze

Minpunten

- Requires Maintenance