



NexaParts B.V.
Duurzaamheidstraat 33
8094SC, Hattemerbroek

E-MAIL info@nexaparts.nl
TEL +31 38 2024038
KVK 87151227

Rod End SIBP22S - GIKR22PB - SIKAC22M - Bore 22MM x M22x1,5 - BSP/F

<https://www.nexaparts.com/rod-end-sibp22s-gikr22pb-sikac22m-bore-22mm-x-m22x15-bspf>

Specificaties

Productnummer SIBP22S - GIKR22PB - SIKAC22M

EAN 7440846263239

Merk NexaParts

Categorie Rod Ends

Materiaal ST 52-3 Verzinkt

Kleur Metaal

Style SIBP22S - GIKR22PB - SIKAC22M

model Stangkop onderhoudsplichtig

Gewicht 0.49 Kg

Color Metaal

Material ST 52-3 Verzinkt

Model Stangkop onderhoudsplichtig

B (Inner ring width) 22 mm

Basic load ratings dynamic 62 kN

Basic load ratings statisch 110 kN

C1 max (Rod end width) 20 mm

CN Radial internal clearance 0,037 - 0,100 mm

d (Bearing bore) 22 mm

d2 max (Rod end diameter) 73 mm

L3 min (Thread length) 43 mm

Maintenance Nippel No

Maintenance required Yes

Norm DIN ISO 12 240-4-series K, Form F

Thread size M22x1,5

Tilting angle 6 ° ?

Total height Rod end (L, L2, L4) 109

Pluspunten

- + DIN ISO 12 240-4-Series K, Form F
- + Easy Essembling
- + Sliding Surface: Steel/bronze

Minpunten

- Requires Maintenance